

SeaShield Paste S105

Petrolatum based compound used for the preparation of metal surfaces

Uses

SeaShield Paste S105 is used to prepare surfaces prior to application of SeaShield Marine Piling Tape.

Composition

SeaShield Paste S105 is a soft petrolatum containing corrosion inhibiting, moisture displacing and flow control additives. SeaShield Paste S105 does not contain any volatile organic material.

Characteristics

SeaShield Paste S105:

- contains no VOC,
- does not dry, harden or crack,
- displaces moisture, and
- requires no special tools for application, and
- may be applied under water.

Surface Preparation

Surfaces should be free from dirt, loose rust, scale or flaking coatings and marine growth.

Application

Apply SeaShield Paste S105 to surfaces with a stiff brush or gloved hand at normal ambient temperatures, including under water.

Application temperature: 0°C to 40°C

Coverage (as primer for SeaShield Tapes):
2-5 m²/kg

Availability

2.5 kg plastic tub
25 kg metal pail

Storage Conditions

Store all components in original packaging in a cool, dry area.

Typical Properties

Flash point	>180°C
Service temperature	-30° to 50°C
Specific gravity (25°C)	1.08
Solids Content	100%

SeaShield International pursue a policy to develop and continually improve all of our products and therefore the information given in this data sheet is intended as a general guide and does not constitute a warranty of specification. However, our sales personnel are committed to assist the user in establishing the suitability of the product for its intended purpose and additional specific information is available on request. SeaShield products are sourced from a company complying with BS EN ISO 9001 Quality Management System.

Revision date: 27/05/2016

SeaShield International
33-35 Chapel Road,
London SE27 0TR, United Kingdom



Tel: +44 (0) 20 8670 7511
Fax: +44 (0) 20 8761 2456
Email: mail@seashield.com
Web: www.seashield.com